

# SpiroPlus AntiFreeze HC

## Application

SpiroPlus AntiFreeze is a highly concentrated treatment product for protecting closed water-carrying systems.

This product is used in water-carrying systems, which may be sensitive to freezing (e.g. air-cooled cooling systems, heat pumps). When using SpiroPlus AntiFreeze, the system does not need emptying in periods of inactivity without the risk of causing damage to the system. The degree of dilution of SpiroPlus AntiFreeze determines the temperature to which the system is protected against freezing. As a diluent you can use both hard (max. total hardness of 30° dH or 535 mg/l CaCO<sub>3</sub>) and softened water.

## Specifications

SpiroPlus AntiFreeze is a highly concentrated mixture based on monopropylene glycol. This mixture provides excellent corrosion and scale protection and effectively protects different materials against corrosion, including brass and aluminium. In addition, SpiroPlus AntiFreeze is chemically and thermally stable, thus guaranteeing an excellent performance of the inhibitor even in high temperature conditions.

## Checking

The dosage can be adjusted through determination of the freezing point.

## Dosage

The dosage of SpiroPlus AntiFreeze strongly depends on the required lowering of the freezing point, as shown in the table below:

Freezing point in °C	Dosage in %v/v
- 10	25%
- 17	35%
- 22	40%
- 35	50%

Concentrations of SpiroPlus AntiFreeze below 25 and above 50% (v/v) are advised against.

## Safety regulations

Spiroplus AntiFreeze is a safe product. Nevertheless, if there is any contact with the skin or the eyes during use, it is always advisable to amply rinse with water.

## Packaging

SpiroPlus AntiFreeze is available in polyethylene containers of 2½, 10, 60 and 200 litres.

## Remarks

Before filling the system, clean the entire system in order to remove all rust particles.

Additionally, we advise you to install a dirt separator for retaining the optimum quality of the glycol solution.

For further information please contact Spirotech bv.

---

All information provided is correct according to our current knowledge. None of the instructions, compositions or applications described here are intended to violate existing patents. Nothing from this documentation may be copied and/or reproduced without our permission. The user remains responsible for checking the suitability of this product for use with respect to the application intended. Therefore we can not accept any liability for damage of any nature resulting from the use of these data or the product concerned.

---